

Hurd's Custom Machinery, Inc.

Explosive Ordnance Device Trailers...

"FEATURES MAY BE MODIFIED TO MEET YOUR NEEDS ON ALL MODELS."

Standard Features - Model 200

Model 200 - 15'



Trailer

- Frame is all steel construction from 3" x 5" tubing with four cross braces.
- Platform covered with 3/4" x #10 expanded metal for traction and cleanliness.
- Full Fenders of 12-gauge steel, top covered with expanded metal.
- Storage compartment 56" x 18" x 16", located on front of 17' & 20' trailers. Other storage area built into catwalk.
- Hitch 2 5/16" ball with jack stand. Pintle hitch on request.
- Robot transport area available on 17' & 20' trailers.
- **LENGTH: 15', 17' OR 20'. , WIDTH: 7'**
- **WEIGHT: approx. 6,500 lbs.**

Bomb Tube

- Tube: Double wall 5/8 high-grade steel with full bottom. Outside tank diameter is 42". Inside tank diameter is 34".

Battery

- Battery: 12v deep cycle battery located built-in battery box in catwalk. 1 1/2 amp battery conditioner. Master switch and identification light.

Lighting System

- Electrical includes eight clearance, four stop/turn and three halogen flashing warning lights.
- Lighting system LED.

Options

- Robot ramps. Spare tire and flip placards

Hoist

- Hoist: Single cylinder lift arm 360° manual rotation, electric cable winch controlled by remote. Includes pendant station with 100' cord.

Axles and Wheels

- Axles: Dual Torflex axles to meet 12,000 G.V.W. Electric brakes on both axles.
- Tires & Wheels: Radial tires with 16" 8-hole wheels.

Painting

- Paint: Our trailers are Sandblasted and then Powder Coated in a choice of colors for a long lasting durable finish.

Accessories

- Internal tube holding net.



Model 200 - 17'



Model 200 - 20' Fully Loaded



Model 200